

*keep a **SharpEye™** on your safety*



40/40M

Multi IR Flame Detector

Superior performance, reliability and immunity to false alarms



SharpEye™

The new 40/40M Multi IR Flame Detector is specifically designed for detection of hydrocarbon and hydrogen flames. It detects hydrocarbon-based fuel and gas fires at long distances with the highest immunity to false alarms. The 40/40M can detect a gasoline pan fire at 215 ft (65m) or a hydrogen flame at 100 ft (30m) in less than 5 seconds.

The 40/40 Series is the most durable and weather resistant range of flame detectors currently on the market. Its new features include a heated window, to eliminate condensation and icing; HART capabilities, for digital communications; lower power requirements, and a compact, lighter design.

Due to increased reliability, the 40/40 Series warranty period has been extended to 5 years and is approved to IEC 61508 Safety Integrity requirements of SIL2.

CONTACT INFORMATION

GasTech Australia Pty Ltd
24 Baretta Rd
Wangara Western Australia 6065
Tel 1800 999 902
Fax 1800 999 903
<http://www.gastech.com.au>



FEATURES & BENEFITS

- Multi Spectrum Design - for long distance detection of hydrocarbons and hydrogen flames
- High false alarm immunity
- Sensitivity Selection - to ensure no zone crossover detection
- Automatic and Manual Built-In-Test (BIT) - to assure continued reliable operation
- Heated window - for operation in harsh weather conditions (snow, ice, condensation)
- Multiple output options for maximum flexibility and compatibility
 - Relays (3) for Alarm, Fault and Auxiliary
 - 0-20mA (stepped)
 - HART Protocol for maintenance and asset management
 - RS-485, Modbus Compatible
- High Reliability - MTBF - minimum 150,000 hours
- Approved to Safety Integrity Level 2 (SIL2 - TUV)
- 5-Year Warranty
- User Programmable via HART or RS-485
- Ex approved for Zone 1 hazardous area location
 - ATEX
 - IECEx
 - FM
 - CSA
- 3rd party Performance Tested
 - EN54-10 (LPCB)
 - FM3260 (FM)

APPLICATIONS

Offshore Oil & Gas installations
Onshore Oil & Gas installations and pipelines
Chemical plants
Petrochemicals plants
Storage Tank farms
Aircraft hangars
Power Generation facilities
Pharmaceutical Industry
Printing Industry
Warehouses

Automotive Industry
Explosives & Munitions
Waste Disposal facilities
Hydrogen Fuel Cell Industry
Hydrogen Vehicle Parking & Refueling
Battery Charging areas
Refinery Hydrogenation
Space Industry hydroxyl propellant
Static Fuel Cell systems

*keep a **SharpEye**™ on your safety*

GENERAL SPECIFICATIONS

Spectral Response	Multi IR Bands					
Detection Range (at highest Sensitivity Setting for 1ft ² (0.1m ²) pan fire)	Fuel	ft / m	Fuel	ft / m	Fuel	ft / m
	n-Heptane	215 / 65	Ethanol 95%	135 / 40	LPG *	100 / 30
	Gasoline	215 / 65	Methanol	115 / 35	Polypropylene Pellets	16 / 5
	Diesel Fuel	150 / 45	IPA (Isopropyl Alcohol)	135 / 40	Office Paper	33 / 10
	JP5	150 / 45	Hydrogen*	100 / 30	* 20" (0.5m) high, 8" (0.2m) width	
	Kerosene	150 / 45	Methane*	100 / 30	plume fire	
	Response Time	Typically 5 seconds				
Adjustable Time Delay	Up to 30 seconds					
Sensitivity Ranges	4 Sensitive ranges for 1 ft ² (0.1m ²) n-heptane pan fire from 50 ft (15m) to 215 ft (65m)					
Field of View	Horizontal 90°; Vertical 90°					
Built-in-Test (BIT)	Automatic (and Manual)					
Temperature Range	Operating:	-67°F to +167°F	(-55°C to +75°C)			
	Option:	-67°F to +185°F	(-55°C to +85°C)			
	Storage:	-67°F to +185°F	(-55°C to +85°C)			
Humidity	Up to 95% non-condensing - withstands up to 100% RH for short periods					
Heated Optics	To eliminate condensation and icing on the window					

ELECTRICAL SPECIFICATIONS

Operating Voltage	24 VDC nominal (18-32 VDC)
Power Consumption	Standby: Max. 100mA (150mA with heated window) Alarm: Max. 150mA (200mA with heated window)
Cable Entries	2 x 3/4" - 14NPT conduits or 2 x M25 x 1.5 mm ISO
Wiring	12 - 22AWG (2.5mm ² - 0.3mm ²)
Electrical Input Protection	According to MIL-STD-1275B
Electromagnetic Compatibility	EMI/RFI protected to EN50130-4
Electrical Interface	The detector includes twelve (12) terminals with five (5) wiring options (factory set)

OUTPUTS

Relays	Alarm, Fault and Auxiliary SPST volt-free contacts rated 5A at 30 VDC or 250 VAC.		
0-20mA (stepped)	Sink (source option) configuration Fault: 0 +1mA Warning: 10mA ± 5% BIT Fault: 2mA ± 10% Alarm: 15mA ± 5% Normal: 5mA ± 10% Resistance Loop: 100-600 Ω		
HART Protocol	HART communication on the 0-20mA analog current (FSK) - used for maintenance, configuration changes and asset management		
RS-485	RS-485 Modbus compatible communication link that can be used in computer controlled installations		

MECHANICAL SPECIFICATIONS

Materials	- Stainless Steel 316L with electro polish finish - Heavy duty copper free aluminum (less than 1%), red epoxy enamel finish		
Mounting	Stainless Steel 316L with electro polish finish		
Dimensions	Detector	3.5" x 4.5" x 6.1" (90 x 114 x 156 mm)	
Weight	Detector (St.St.)	5.5 lb	(2.5 kg)
	Detector, aluminum	2.5 lb	(1.2 kg)
	Tilt mount	2.2 lb	(1.0 kg)
Environmental Standards	Meets MIL-STD-810C for Humidity, Salt & Fog, Vibration, Mechanical Shock, High Temp, Low Temp		
Water and Dust	IP66 and IP67 per EN60529, NEMA 250 6P		

APPROVALS

Hazardous Area	ATEX and IECEx	Ex II 2 GD, Ex de IIB+H2 T5 (-55°C to + 75°C) Ex tD A21 IP66/X7 T 95°C Class I Div. 1, Groups B, C & D Class II/III Div. 1, Groups E, F & G	Ex de IIB+H2 T4 (-55°C to + 85°C) Ex tD A21 IP66/X7 T 105°C
Performance	EN54-10 (LPCB) FM-3260 (FM)		
Reliability	IEC61508 - SIL2 (TUV)		

ACCESSORIES

Fire Simulator	20/20-313	Weather Protector	777163	Laser Pointer	777166
Tilt Mount	40/40-003	Air Shield	777161	(Detector area coverage)	