

ACG+

Compressed Breathing Air Monitor



Key Features:

- Portable or fixed
- Mains, DC and up to 12 hour rechargeable battery power options
- Proprietary dew point sensor lock out system for fast start up - ideal for multi point checking
- Proprietary humidifier option for continual use to prolong electrochemical sensor lives (CO & O₂)
- Fast-connect purge system - helps ensure accurate readings in minutes
- Robust carry case
- Sensors now even easier to change out
- NiMH or Lithium battery options
- 90 days of datalogging easily retrieved via USB connection

Looking after the air you breathe

The ACG+ is a unique compressed breathing air monitor designed to be used in a fixed installation near your air compressor or as an ideal portable solution for multi-point air monitoring.

The ACG+ offers the user peace of mind as it continually monitors Oxygen (O₂), Carbon Dioxide (CO₂), Carbon Monoxide (CO), dew point (H₂O) and Volatile Organic Compounds (VOC) and also has a sample port to check for oil mist. Continual monitoring or periodic checking of these parameters aids the user in achieving compliance with breathing air standards and other local regulations, whilst ensuring those employees breathing the air are safeguarded against potentially fatal contamination issues. Housed in a robust case when used portably or in a purpose built housing when used in a fixed position, the ACG+ is simple to install, use and maintain and has a low cost of ownership.

The ACG+ offers 90 days of datalogging, easily retrieved with a USB connection and has audio/visual alarms and a common relay to connect to a beacon or to shut down the compressor should an alarm be triggered.

Employers have a duty of care to their employees to ensure the air they breathe is of the best quality possible and contaminants such as CO and VOCs are maintained at very low levels as they can cause serious health effects, particularly as the effects of such contaminants are increased at pressure. Even new, well-sited and well-maintained compressors can sometimes fail and contaminants can also enter into the breathing air through the intake. As this can theoretically happen at any time, continual monitoring is a safer and more accurate best practice than "spot checking" such as using colorimetric tube testing kits at intervals.

The ACG+ can be used with any breathing air compressor and simply needs to be connected after the compressor and before the end user (or cylinder) to ensure that contaminants can be detected before they reach the intended destination. The pressure needs to be regulated down to between 5 to 10 Bar. The ACG+ is most commonly situated in the compressor room but when used portably it can be used in most environments.

Compressed Breathing Air Monitor

Sensor specifications:

Oxygen:	Range: 0 to 50% Accuracy: $\pm(0.035\% \text{ O}_2 + 1\% \text{ of reading} + 0.15\% \text{ of reading}/^\circ\text{C})$ Technology: Analox MEC intelligent electrochemical oxygen sensor
Carbon Dioxide:	Range: 0 to 1000ppm Accuracy: $\pm(25\text{ppm CO}_2 + 1\% \text{ of reading} + 1\text{ppm CO}_2/^\circ\text{C})$ Technology: Analox 5S3 intelligent NDIR sensor
VOC:	Range: 0 to 100ppm Accuracy: $\pm(1\text{ppm VOC} + 5\% \text{ of reading} + 0.25\% \text{ of reading}/^\circ\text{C})$ Technology: Analox MEC intelligent PID sensor
Carbon Monoxide:	Range: 0 to 20ppm Accuracy: $\pm(1\text{ppm CO} + 5\% \text{ of reading} + 0.1\text{ppm CO}/^\circ\text{C} + 0.5\% \text{ of reading}/^\circ\text{C})$ Technology: Analox MEC intelligent electrochemical sensor
Water Vapour:	Range: 0 to 100mg/m ³ Accuracy: $\pm(0.15\text{mg/m}^3 \text{ H}_2\text{O} + 20\% \text{ of reading})$ Technology: Water vapour sensor using capacitive technology

Analyser specifications:

Weight:	12 Kg
Power:	Input voltage: 24V DC Power consumption: 24 W (max)
Optional Power Supply:	Universal mains adaptor; Input: 95 to 250VAC, 50/60Hz
Sensor Response Time:	T90 < 120 secs T90 < 15 mins (water vapour sensor)
Flow Rate:	5 LPM (max)
Inlet Pressure:	5 to 10 bar gauge
Operating temperature:	-5°C to 50°C
Storage temperature:	-10°C to 60°C
Humidity:	0 to 99% RH (non condensing)
Environmental protection rating:	IP54
Outputs:	1x Normally open relay contact 1x Normally closed relay contact 3x 24V DC switched outputs
Certification and Approvals:	BS EN 12021, DEF STAN 68-284, Navsea, SS521-AK-1-010, US Navy Dive Manual and BS 8478

Part Number: 72-8050-ACG

HEAD OFFICE

Telephone +61 8 6108 0000
Facsimile +61 8 9408 1868
Email info@gastech.com.au
24 Baretta Road
Wangara, Western Australia 6065

NSW OFFICE

Telephone +61 2 9451 0054
Facsimile +61 2 9450 0833
Email info@gastech.com.au
21/25, Narabang Way
Belrose NSW 2085

