

# B-Guard Ir

## Infrared Hydrocarbon Gas Detector



GasTech Australia Blind Guard series B-Guard™ Series GHD hydrocarbon detector is a single source dual wavelength instrument. The sensing and reference elements are self-compensating for optical integrity and other signal inhibitors. The industry standard 4 -20 mA analog output provides remote alarm, fault and calibration signals.

### Features

- Continuous detection of combustible gas in explosion hazardous area with flame proof structure
- State of art Infra red detection principle
- Long service life (more than 5 years)
- Low operation cost due to maintenance free
- Operation at no oxygen environment
- Self diagnosis function with built-in Microprocessor
- Rapid response time (with 10 secs)
- 4-20mA DC output signal
- Easy configuration of monitoring system with RS-485 Modbus(isolated) Serial communication function

### Applications

- Refineries
- Gas turbines
- Drilling and production platforms
  - Chemical plants
  - Fuel loading facilities
  - Compressor stations
  - Oil well logging
- Wastewater treatment facilities
  - LNG/LPG processing and storage facilities
  - Transportation facilities

# B-Guard Ir

## Infrared Hydrocarbon Gas Detector

<b>Model</b>	B-Guard GHD(Hydrocarbon)
<b>Measuring gas</b>	Combustible gas (LNG, LPG, Methane & etc)
<b>Measuring type</b>	Diffusion type
<b>Sensor type</b>	Infrared type
<b>Measuring range</b>	0-10,000 ppm & 0-100 % LEL 0-10,000 ppm & 0-5.0% Vol
<b>Sensor life time</b>	More than 5 years
<b>Response time</b>	<10 sec / 90% scale
<b>Accuracy</b>	±3% / Full scale
<b>Parameter controls</b>	Non intrusive control with Magnet bar (calibration, maintenance, alarm setting)
<b>Analog output : Measuring signal</b>	4-20 mA DC
<b>Maintenance signal</b>	3 mA DC
<b>Calibration signal</b>	2 mA DC
<b>Fault signal</b>	0 mA DC
<b>Cable / Distance</b>	Power + signal cable: 3 wire (above CVVS 1.5sq) / 500m max.
<b>Conduit pipe</b>	1/2" & 3/4" PF, NPT (3/4" PF standard)
<b>Mounting type</b>	2" Pole mount, Wall mount, Duct mount
<b>Operating temperature</b>	-20°C ~ +50°C
<b>Operating humidity</b>	5 ~ 99%.RH (non-condensing)
<b>Operating power</b>	18 ~ 31V DC (24V DC normal) / 300mA max.
<b>Dimensions</b>	301.5 x 152 x 109 (W X H X D)
<b>Weight</b>	2.5kg
<b>Approval</b>	Flame proof structure (Ex d IIC T6), ATEX, IECEx
<b>Ordering information</b>	67-9092-Ir      S-Guard IR Smart Transmitter, 4-20mA, 0-100% LEL IECEx

Distributed By

Telephone +61 8 6108 0000  
Facsimile +61 6 9408 1868  
Free call 1800 999 902  
Email [info@gastech.com.au](mailto:info@gastech.com.au)  
24 Baretta Road  
Wangara Western Australia 6065

The logo for GASTECH AUSTRALIA features the word "GASTECH" in a large, bold, blue sans-serif font. A stylized blue swoosh or arc is positioned above the "A" in "GASTECH". Below "GASTECH", the word "AUSTRALIA" is written in a smaller, blue, all-caps sans-serif font.