

GasAlertMicroClip XT

Multi-gas detector: H₂S, CO, O₂, LEL



STANDARD FEATURES

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

Multi-gas made simple

The slim and compact GasAlertMicroClip XT provides affordable protection from atmospheric hazards. This multi-gas detector offers continuous visual confirmation of detector operation and compliance with the IntelliFlash™ feature and simple one button operation offers ultimate ease of use and significantly reduces time spent training the user. The GasAlertMicroClip XT is fully compatible with BW's MicroDock II automatic test and calibration system.

- Continuous visual compliance with IntelliFlash
- Multi-gas versatility with one-button simplicity
- Incredibly thin and lightweight, making it comfortable to wear

LIFE SIZE IMAGE!



GasAlertMicroClip XT

Multi-gas detector: H2S, CO, O2, LEL



Typical range of Gases Detected

Gas	Measuring Range	Resolution
H2S	0-100 ppm	1 ppm
CO	0-500 ppm	1 ppm
O2	0 to 30.0%	0.1%
LEL	0 to 100% LEL	1% Alternative display below
CH4	0 to 5.0%v/v	0.1%

* Alarm setpoints for all sensors are user adjustable. Setpoint(s) are automatically displayed during instrument start-up.

Size:	4.4 x 2.4 x 1.1 in. / 11.3 x 6.0 x 2.9 cm
Weight:	6 oz. / 171 g
Temperature:	-4 to +122°F / -20 to +50°C
Humidity:	0% - 95% RH (non-condensing)
Alarms:	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit)
Tests:	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)
Pump:	Compatible with the Sampler motorized sampling pump
Battery life:	10 hours (typical); recharges in less than 4 hours
User options:	Confidence beep, Set STEL interval, Sensor on/off, Latching alarms, Safe display mode, Stealth mode, Calibration lock, Auto zero on start up, O2 auto calibration on start up, Set bump test interval, IntelliFlash interval, Combustible gas measurement (% LEL or % by volume methane), User-settable calibration gas level, Force bump test when overdue, Force calibration when overdue, Low alarm acknowledge, Language choices (five), Set custom start up message
Ratings:	EMI/RFI: Complies with EMC Directive 2004/108/EC IP66/IP67
Certifications and approvals:	CSA Class I, Div. 1, Gr. A, B, C, D IECEX: Ga Ex ia IIC T4 ATEX: CE II 1 G Ga Ex ia IIC T4
Warranty:	Full two year warranty including all sensors

Part Number: 72-8056-01

Options and Accessories:



MicroDock II compatible
PN: 81-8018-11



Auxiliary filter kit
PN: 33-4000



IR connectivity kit
PN: 82-9994



Five unit cradle charger
PN: 49-8001-15

Honeywell

HEAD OFFICE

Telephone +61 8 6108 0000
Facsimile +61 8 9408 1868
Email info@gastech.com.au
24 Baretta Road
Wangara, Western Australia 6065

NSW OFFICE

Telephone +61 2 9451 0054
Facsimile +61 2 9450 0833
Email info@gastech.com.au
21/25, Narabang Way
Belrose NSW 2085

GASTECH
AUSTRALIA