

# H-Guard-D™

## CO2 Transmitter



The H-Guard-D is a CO2 transmitter series designed to be installed in HVAC return air ducts. The CO<sub>2</sub> sensing element uses the Non-Dispersive Infrared Technology (NDIR) with the patented self-calibration system to guarantee the long term stability and up to 15 years life time. TG9 duct probe transmitter offers temperature and humidity option. The high accuracy temperature and humidity combined sensor provide a digital interface and outstanding full range linearity. The one or three analog 0-10V or 4~20mA outputs are selectable by jumpers. Modbus RS485 communication interface is provided. Optional backlit LCD can display all measurements and is usable easily in more applications. TG9 offers simplicity in design and installation with the special demountable and replaceable filter to avoid pollution and influence of measurement.

### Typical Applications:

Building management for office areas and residential

Ventilation control system

### Key Features:

- Special used to real-time detect CO2 level in air ducts.
- NDIR infrared CO2 sensor inside with Self-Calibration and up to 15 years lifetime
- Humidity and temperature detection optional
- Combined temperature and humidity sensor provide the highest accuracy in full range
- Backlit LCD display option can display CO2 measurement and temperature+ RH measurements
- Providing one or three 0~10VDC or 4~20mA or 0~5VDC analog outputs
- Modbus RS485 communication interface makes usage and test more convenient
- Smart structure and attractive housing provide you a unique operation feeling
- Simple and skillful design and installation with a demountable and replaceable filter to provides dust-proof protection
- Special a 180° rotatable fastness position for the probe can change the direction of air detection.
- All housing and probe are IP54 class
- CE-Approval

# H-Guard-D™

## Sensor & Transmitter Specifications

<b>Gas detected</b>	Carbon Dioxide (CO <sub>2</sub> )
<b>Sensing element</b>	Non-Dispersive Infrared Detector (NDIR)
<b>Accuracy@25(77),2000ppm</b>	±40ppm + 3% reading
<b>Stability</b>	<2% of FS over life of sensor (15 yr typical)
<b>Calibration interval</b>	ABC Logic Self Calibration System
<b>Response time</b>	<2 minutes for 90% step change
<b>Warm up time</b>	2 hours (first time) 2 minutes (operation)
<b>CO<sub>2</sub> measuring range</b>	0-2,000ppm / 0-5,000ppm selectable in orders
<b>Sensor life</b>	Up to 15 years
<b>Power supply</b>	24VAC/24VDC
<b>Consumption</b>	1.5 W max. ; 0.8 W avg.
<b>Analog outputs</b>	0~10VAC or 4~20mA selectable by jumpers
<b>Relay output</b>	1X3A switch load
<b>Modbus interface</b>	Four set points selectable by jumpers Modbus RS485 interface 9600/14400/19200(default)/28800 or 38400bps (programmable selection), 15KV antistatic protection.
<b>Operation conditions</b>	0~50(32~122); 0~95%RH, non condensing
<b>Storage conditions</b>	-40~70(-40~158)
<b>Net weight</b>	240g
<b>Dimension</b>	Junction box 100mm×85mm×50mm Probe 124.5mm x 40mm
<b>Approval</b>	CE-Approval
<b>Ordering information</b>	65-9081 H-Guard-D CO <sub>2</sub> Transmitter, 1x4-20mA output 1 x Relay output 0-2000ppm standard range 49-998-01Plug pack 240VAC/24Vdc 450mA

Distributed By

Telephone 1800 999 902  
Facsimile 1800 999 903  
Int. Phone 61 8 9242 1869  
Int. Fax 61 8 9242 1959  
Email [info@gastech.com.au](mailto:info@gastech.com.au)  
24 Baretta Road  
Wangara Western Australia 6065

**GASTECH**  
AUSTRALIA