

# ppbRAE 3000

## Portable Handheld VOC Monitor



### Key Features:

#### Proven PID technology

- 3-second response time
- Extended range from 1 ppb to 10,000 ppm with best in class linearity
- Humidity compensation with integral humidity and temperature sensors

#### Integrated

- Real-time wireless data transmission through built-in Bluetooth & RAElink3 link
- Integrated Correction Factors list of 220 compounds—more than any other PID
- Includes flashlight for dark conditions
- Large graphic display presents gas type, correction factor & concentration

#### Durable

- Easy access to battery, lamp and sensor in seconds without tools
- Rugged housing withstands use in harsh environments
- IP-67 waterproof design for easy cleaning and decontamination

### Applications:

- Oil & Gas
- HazMat
- Industrial Safety
- Civil Defense
- Environmental & Indoor Air Quality

The compact ppbRAE 3000 is a comprehensive VOC gas monitor and data-logger for hazardous environments. The ppbRAE 3000 is the most advanced handheld VOC monitor available for parts-per-billion detection. This third-generation patented PID device monitors VOCs using a photoionization detector with a 9.8 eV, 10.6 eV UV-discharge lamp. The built-in wireless modem allows real-time data connectivity with the ProRAE Guardian command center located up to two miles/3 km away (with optional RAElink3 portable modem) from the ppbRAE 3000 detector.

### Sensor Specifications

Gas Monitor	Range	Resolution	Response Time T90
VOCs	0 to 9999 ppb	1 ppb	< 3 sec
	10 to 99 ppm	0.01 ppm	< 3 sec
	100 to 999 ppm	0.1 ppm	< 3 sec
	1,000 to 9,999 ppm	1 ppm	< 3 sec

### Monitor only includes:

- ppbRAE 3000 Monitor, with RAE Systems UV lamp, as specified
- Datalogging with ProRAE Studio II
- Charging/download adapter
- VOC Zeroing Tubes (1 box)
- Tube adapter
- Tedlar® bag for calibration
- Flex-I-Probe™
- External filter
- Rubber boot with straps
- Alkaline battery adapter
- Lamp-cleaning and tool kit
- Operation CDROM
- Operation & Maintenance manual
- Soft leather case

### Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- Charging/download cradle
- 5 Porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

### Optional calibration kit adds:

- 10 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

# ppbRAE 3000

## Portable Handheld VOC Monitor

### Analyser specifications:

Size:	10" L x 3.0" W x 2.5" H (25.5 cm x 7.6 cm x 6.4 cm)
Weight:	26 oz (738g)
Sensor:	Photoionization sensor with standard 10.6 eV or optional 9.8 eV lamp
Battery:	<ul style="list-style-type: none"><li>- Rechargeable, external field-replaceable Lithium-Ion battery pack</li><li>- Alkaline battery adapter</li></ul>
Operating Hours:	16 hours of operation (12 hours with alkaline battery)
Display Graphic:	4 lines, 28 x 43 mm, with LED backlight for enhanced display readability
Keypad:	1 operation and 2 programming keys, 1 flashlight on/off
Direct Readout:	Instantaneous reading <ul style="list-style-type: none"><li>- VOCs as ppm by volume or mg/m<sup>3</sup></li><li>- STEL, TWA and PEAK</li><li>- Battery and shutdown voltage</li><li>- Date, time, temperature</li></ul>
Alarms:	95 dB (at 12"/30 cm) buzzer and flashing red LED to indicate exceeded preset limits <ul style="list-style-type: none"><li>- High: 3 beeps and flashes per second</li><li>- Low: 2 beeps and flashes per second</li><li>- STEL and TWA: 1 beep and flash per second</li><li>- Alarms latching with manual override or automatic reset</li><li>- Additional alarm for low battery and pump stall</li></ul>
EMI/RFI:	Highly resistant to EMI/RFI Compliant with EMC Directive 89/336/EEC
IP Rating:	<ul style="list-style-type: none"><li>- IP-67 unit off and without flexible probe</li><li>- IP-65 unit running</li></ul>
Datalogging:	Standard 6 months at one-minute intervals
Calibration:	Two-point or three-point calibration for zero and span Calibration memory for 8 calibration gases
Sampling Pump:	<ul style="list-style-type: none"><li>- Internal, integrated flow rate at 500 cc/mn</li><li>- Sample from 100' (30m) horizontally and vertically</li></ul>
Low Flow Rate:	Auto pump shutoff at low-flow condition
Communication:	<ul style="list-style-type: none"><li>- Download data and upload instrument set-up from PC through charging cradle or optional Bluetooth™</li><li>- Wireless data transmission through built-in RF modem</li></ul>
Wireless Network:	ProRAE Guardian Real-Time Wireless Safety
Wireless Emergency:	ISM license-free bands
Wireless Range (Typical):	ppbRAE 3000 to RAELink3 or RAELink3 Z1 modems ~ 33 feet (10 meters)
Hazard Area Approvals:	<ul style="list-style-type: none"><li>- US and Canada: UL, cUL, Classified as Intrinsically Safe for use in Class I, Division 1 Groups A, B, C, D</li><li>- Europe: ATEX Ex II 2GEx ia IIC/IIB T4</li><li>- IECEx: Ex ia IIC/IIB T4</li></ul>
Temperature:	-4° to 113° F (-20° to 50° C)
Humidity:	0% to 95% relative humidity (non-condensing)
Attachments:	Durable black rubber boot with straps
Warranty:	3-year warranty for 10.6 eV lamp 1 year for pump, battery and instrument

**Part Number: 72-8020-R**

### HEAD OFFICE

Telephone +61 8 6108 0000  
Facsimile +61 8 9408 1868  
Email [info@gastech.com.au](mailto:info@gastech.com.au)  
24 Baretta Road  
Wangara, Western Australia 6065

### NSW OFFICE

Telephone +61 2 9451 0054  
Facsimile +61 2 9450 0833  
Email [info@gastech.com.au](mailto:info@gastech.com.au)  
21/25, Narabang Way  
Belrose NSW 2085

