



Real-Time DPM Measurement as a Maintenance Tool



@ Mining Diesel Emissions Council Conference 2010
October 5-9th, Toronto

Presentation:

Peter Anyon PM-Tech / MAHA



Developing a DPM Management Strategy



Research / Evaluation

Government Responses

Pre-Program DPM Emission Profiles

Test Equipment

Implementation

Program Effectiveness

Summary & Conclusions



Research



- **An intensive testing and evaluation study undertaken by The Australian Coal Industry's Research Program (ACARP) and coordinated by the New South Wales Department of Primary Industry's Mines Technical Services Division**
 - in conjunction with SIMTARS , NIOSH
 - supported by external consultants and industry
 - over the period 2000~2002
- **Aim:** *“...to find one or more methods for measuring diesel particulate matter (DPM) in the raw exhaust of diesel-powered mining equipment at underground coal mines”.*



Test Program Structure



Dynamometer Testing

- of candidate instrument performance and comparison
- Evaluation of suitability for DPM testing under closely controlled conditions
- 3 engines (Cat 3306, Kia 4100, Cat 3126)
- 4 instruments (three laser light-scattering, one pressure drop)
- tested over 8 steady state and two transient modes
- results correlated with traditional gravimetric filter method



Test Program Structure




Field Testing


- **five New South Wales mines selected as test sites**
- **where feasible, multiple instruments were operated in parallel**
- **mixture of steady-state and transient tests used**
- **tests included free acceleration, idle and acceleration/power modes with torque converter engaged**

Key Project Outcomes

- **Stall Test**
 - **60-second idle/full power/idle test with drive engaged, using the torque converter as a dynamometer.**



- **Free Acceleration Test**
 - for plant with no torque converter, three full-throttle accelerations (gear in neutral) to governed speed, spaced over 60 seconds





Initial Government Response (Summary)



Primary Guidelines

- ambient DPM exposure limit 0.1mg/m³ elemental carbon (EC). EC to be calculated as equivalent to 0.5 x total suspended diesel particle mass
- all new engines to have “signature” test before entering service
- all existing engines to be maintained to “best” emissions level then have “signature” test
- periodic (max 4 week intervals) testing to monitor condition and trigger rectification if DPM exceeds limit (initially 30% > than signature, soon to be 20%)
- records to be maintained of all test results for individual vehicles/plant



Pre-Program DPM Emission Profiles




Preliminary fleet testing was performed at several mines to characterize the emission profiles of vehicles.

Results of this testing showed considerable similarities

- most engines had low - moderate emissions, with a few very high emitters peaking the curve**




DPM Emission Distribution: Initial Survey (Example 1)





DPM Emission Distribution: Initial Survey (Example 2)




Correlations, Test Cycle vs On-Task Operation



On-Vehicle Testing



On-Board Real Time Recording




Custom software (available with instrument) stores and charts continuous DPM Concentration vs Time for analysis and correlation studies

Correlation, Example 1




			Static Test	Min	Max	Average
				6.7	194	58.1
	Average =	58.16394	Engine hours	6758		
			Last 1000 service	0		



Correlation, Example 2




Static Test	Min	Max	Average
	20.5	66	36.5
Engine hours	7822		
Average = 34.34803	Last 1000 service	676	



Correlation, Example 3



Static Test	Min	Max	Average
	6.6	416	48.8
Average =	38.0728		



PM
Tech

Implementation



- **Third generation laser light scattering (LLSP) is now the measuring method of choice in Australia**
- **Incorporates several years of experience and industry feedback**
- **Simple one-button operation**
- **Auto-zero before every test**
- **NiMH Battery, >2hrs testing**
- **Remote control for single person testing**
- **On-screen and flashing LED operator prompts**
- **Automatic test result generation**
- **Simple field calibration and service**





PM
Tech

MPM-4M (4th Generation)



Peter Anyon - 06 October 2010 - All use and right of disposition such as copying and right of passing on this presentation remain with MAHA Maschinenbau Haldenwang GmbH & Co.. KG. and PM-Tech (a division of MicroCAD Australia Pty Ltd)

Stall Test DPM Results (Typical)



Test Result Screen (Example)

Test Result	142	mg/m ³	EC
Supplementary Data			
Average conc (Idle Modes)	75.1	mg/m ³	EC
Average conc (Full Power)	277	mg/m ³	EC
Minimum concentration	0.00	mg/m ³	EC
Maximum concentration	545	mg/m ³	EC
Record Test Results, then press ENTER to start new test			

Second-by-second test data can also be exported directly to PC via RS232/USB

Testing Program




- **Every vehicle and item of plant operating underground is tested (minimum) monthly. Most mines test every 2 weeks or weekly.**
- **DPM result >20% above “signature” level for that vehicle mandates maintenance/repair before returning underground.**
- **Absolute DPM limits are also applied (next slide)**
- **A standardized diagnostic tree is generally used to identify and rectify high emissions, based on cost/frequency analysis (eg, start with air filter and work down from there)**


DPM Limit Progression (Stall Test)



Limit DPM Concentration (mg/m³) by Year



Program Effectiveness (Example)



Average DPM Reduction = 60%



Benefits (Health & Economic)



- **Program minimizes DPM exposure risk to underground personnel**
- **Measured Maintenance also optimizes fuel consumption and has potential to improve engine reliability.**
- **By maintaining “On-Condition”, wastage costs due to unnecessary maintenance are avoided.**
- **Assigning specific cubic flow requirements to individual vehicles allows optimization of equipment deployment and ventilation flows, without exceeding DPM exposure levels**



Summary



- **DPM measurement is now broadly accepted as a necessary and integral part of mine equipment and ventilation management.**
- **Test cycles and test equipment have proved to be practical and effective**
- **Continuing dialogue and cooperation between and within industry and government has been essential for effective program implementation**



Last Word



Measured Maintenance

**“IF YOU CAN’T MEASURE IT
YOU CAN’T FIX IT”**