

GasAlertClip Extreme

Single Gas Detector: H₂S / CO / SO₂/ O₂



STANDARD FEATURES

- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Compatible with BW MicroDock II automatic test station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot
- Records and transmits gas alarm events
- Large confidence LCD displays life remaining in months, days and hours

Up to three years of continuous maintenance-free protection

As the world's most popular and widely used zero-maintenance gas detector, the GasAlertClip Extreme offers continuous, reliable protection. Available in two year or three year versions, this single gas detector requires no calibration, sensor replacement, battery replacement or battery charging. Compatible with the MicroDock II automatic test system, the simplicity of the GasAlertClip Extreme combined with minimal training requirements and negligible maintenance costs, make the GasAlertClip Extreme one of the most cost-effective PPE solutions for facility workers and on-site contractors.

- Durable, reliable and easy to use with no downtime
- Record keeping is accurate and easy with automatic event logging
- Exceptionally low cost of ownership
- User-selectable alarm setpoints (5/10 or 10/15) on the H₂S, 2 year model

LIFE SIZE IMAGE!



GasAlertClip Extreme

Single Gas Detector: H₂S / CO / SO₂/ O₂



Typical range of Gases Detected

| Gas | Measuring Range | Low Alarm Level | High Alarm Level |
|-----------------------------|--------------------|-----------------------|------------------|
| 2 or 3 year detector | | | |
| H ₂ S | 0 - 100 ppm | 10 ppm* | 15 ppm* |
| CO | 0 - 300 ppm | 35 ppm (30 ppm UK/EU) | 200 ppm |
| 2 year detector only | | | |
| SO ₂ | 0 - 100 ppm | 5 ppm | 10 ppm |
| O ₂ | 0 - 30.0 % by vol. | 19.5 % | 23.5 % |

*User-selectable (5 ppm Low/10 ppm High or 10 ppm Low/15 ppm High) on H₂S 2 year model
Alarm setpoints are not user adjustable. If different setpoints are required, please indicate at time of order

Note: H₂S, CO and SO₂ sensors do not require calibration; the O₂ sensor is self-calibrating.
A regular pump testing regime is recommended as per AS.

| | |
|-------------------------------|--|
| Size: | 1.1 x 2.0 x 3.2 in. / 2.8 x 5.0 x 8.1 cm |
| Weight: | 2.7 oz. / 76 g |
| Temperature: | H ₂ S: -40 to +122°F / -40 to +50°C CO: -22 to +122°F / -30 to +50°C SO ₂ : -22 to +122°F / -30 to +50°C O ₂ : -4 to +122°F / -20 to +50°C |
| Humidity: | 5% - 95% RH (non-condensing) |
| Alarms: | - Visual, vibrating, audible (95dB) - Low, High |
| Tests: | Full function self-test on activation and every 20 hours, and automatic battery test every 2 hours |
| Battery life: | Two years (H ₂ S, CO, SO ₂ or O ₂) or three years (H ₂ S or CO) |
| Ratings: | EMI/RFI: Complies with EMC Directive 89/336/EEC |
| Certifications and approvals: | CSA Class I, Div. 1, Gr. A, B, C, D IECEX: Ex ia IIC T4 ATEX: CE II 1 G T4 Ex ia IIC T4 |
| Warranty: | 2 or 3 years from activation (given normal operation), plus 1 year shelf life |

Part Number:
72-9026-CO
72-9026-H₂S
72-9026-O₂
72-9026-SO₂

Options and Accessories:



MicroDock II
compatible

PN: 81-8018-11



Concussion-proof boot

PN: 21-9024



IR Data Link

PN: GA-USB2

Honeywell

Telephone +61 8 6108 0000
Facsimile +61 8 9408 1868
Email info@gastech.com.au
24 Baretta Road
Wangara, Western Australia 6065

GASTECH
AUSTRALIA