

VENTIS SLIDE-ON PUMP

Ventis™ MX4 and Ventis™ Pro Series compatible



The Ventis™ Slide-on Pump is ideally suited for operators who wear their gas monitors for personal protection but occasionally require a pump for confined space entries. Available in black or safety orange and powered by its own battery pack, the slide-on pump is compatible with the Ventis™ MX4 and Ventis™ Pro Series Multi-Gas Monitors.

KEY FEATURES

- Convenient sampling – sample draw distance of up to 50 feet
- Easy to attach – no tools required to attach or remove
- Uses same battery packs and chargers as Ventis
- Flexible battery options – 3 available battery options



VENTIS SLIDE-ON PUMP



SPECIFICATIONS Specifications subject to change without notice

Dimensions:	143 x 81 x 68 mm (5.6 x 3.2 x 2.7 in) Lithium-ion battery version 143 x 81 x 85 mm (5.6 x 3.2 x 3.3 in) Extended range lithium-ion battery 143 x 81 x 73 mm (5.6 x 3.2 x 2.9 in) Alkaline battery version	Pump fault alarms:	Ultra-bright LED's Loud audible alarm (90 dB at 30cm)
Weight:	<ul style="list-style-type: none"> • 270 g (9.5 oz) Lithium-ion battery version • 316 g (11.2 oz) Extended range lithium-ion battery • 284 g (10.0 oz) Alkaline battery version 	IP Rating:	Third-party certified IP67
Case material:	Polycarbonate with protective rubber overmold	Warranty:	Two-year warranty excluding consumables (i.e. – filters)
Sample draw capability:	Up to 15.2 m (50 ft)	Certifications	ATEX: Ex ia I Ma and Ex ia IIC T4 Ga; Equipment Group and Category: I M1 and II 1G China Ex: Ex ia IIC T4 Ga CSA: Class I, Division 1, Group A-D, T4; Ex ia IIC T4 GOST-EAC: 0 Ex ia IIC X T4; PO Ex ia I X IECEX: Ex ia IIC T4 Ga INMETRO: Ex ia IIC T4 Ga; IP66; IP67 UL: Class I, Division 1, Groups A-D, T4; Class I, Zone 0, AEx ia IIC T4 Ga; Class II, Group F-G (Carbonaceous and Grain Dust)
Operating temperature range:	-20°C to 50°C (-4°F to 122°F)	Part no.	30-9009
Operating humidity range:	15% to 95% non-condensing (continuous)		
Power source and Run time:	<ul style="list-style-type: none"> • Rechargeable lithium-ion battery pack – 18 hours @ 20°C • Rechargeable extended range lithium-ion battery pack – 36 hours @ 20°C • Replaceable AAA alkaline battery pack – 10 hours @ 20°C 		



t +61 8 6108 0000

e info@gastech.com

w gastech.com

HEAD OFFICE
24 Baretta Road
Wangara WA 6065
Phone: +61 8 6108 0000

SYDNEY OFFICE
21/25 Narabang Way
Belrose NSW 2085
Phone: +61 2 9451 0054

BRISBANE OFFICE
PO Box 349
Cannon Hill Qld 4170
Phone: +61 7 3160 0901