

UNI MP100T & MP300T1

Docking Stations for Single Gas Detectors

The UNI Docking Box (MP100T) and UNI CaliCase (MP300T1) are docking and calibration stations for the UNI and UNI 321 Single Gas Detectors.

The MP100T is a single docking box for one instrument and the MP300T1 handles up to four UNIs simultaneously. They both provide the three functions of;

1. semi-automated calibration or bump testing,
2. data downloading and
3. uploading instrument configuration. In addition, all calibrations and bump tests performed on the docking units are stored in on-board memory as a compliance record.

The docking stations are designed to handle the most commonly measured gases such as oxygen (O₂), carbon monoxide (CO), hydrogen sulfide (H₂S), ammonia (NH₃) hydrogen cyanide (HCN) and sulfur dioxide (SO₂). Both docking systems have rechargeable batteries and are portable for remote use.



- ▲ Docking Box
- ◀ CaliCase Docking Station



KEY FEATURES

- Bump testing, calibration, configuration and data recording on a single platform
- Simple, single-button operation
- Fast – up to 4 units bumped or calibrated simultaneously (on MP300T1)
- 1999 or 100,000 calibration or bump record storage
- Portable, using battery power for up to 1000 bump tests
- Robust – All-in-one hard case

UNI MP100T & MP300T 1

SPECIFICATIONS Specifications subject to change without notice**SINGLE DOCKING BOX MP100T SPECIFICATIONS**

Size	"9.2 x 7.5 x 4.3 in (23.5 x 19.0 x 10.7 cm)"
Weight	3.3 lbs. (1.5 kg)
Number of Units	One (1)
Battery	Rechargeable Lithium battery, up to 1000 bump tests on a single charge
Temperature	-4°F to 122°F (-20°C to 50°C)
Humidity	5 to 95% relative humidity (non-condensing)
Event Log	1999 Calibration or Bump records
Power & Communications Connection	USB (Type A)
Test Gas Supply	"• Cylinder & demand flow regulator (not included) outside Docking Box • Built-in pump for air or test gas"
Gas Connections	"• Quick-connects for 6-mm o.d. tubing: • Test gas inlet for calibration/bump • Air inlet for zeroing • Exhaust outlet for guiding toxic gases away from operator"
Recommended Gases	All gases offered in UNI sensors except for ozone, chlorine dioxide, hydrogen chloride, and hydrogen fluoride
Safety Certifications	For use in non-hazardous locations
Warranty	1 year

CALICASE (MP300T1) SPECIFICATIONS

Size	"21.9 x 14.1 x 7.3 in (55.6 x 35.8 x 18.5 cm)"
Weight	20 lbs. (9.1 kg)
Number of Units	Up to Four (4)
Battery	"Rechargeable Lithium battery, up to 1000 bump tests (4000 instrument tests) on a single charge"
Temperature	-4°F to 122°F (-20°C to 50°C)
Humidity	5 to 95% relative humidity (non-condensing)
Event Log	100,000 Calibration or Bump records
Power & Communications Connection	USB (Type A)
Test Gas Supply	"• Cylinder (not included) & regulator inside CaliCase • Built-in pump for air or test gas"
Gas Connections	"• C-10 Demand-flow regulator and all gas supply connections included • Exhaust outlet hose barb for guiding toxic gases away from operator"
Cylinder Specifications	"• Max 14.25 x 3.5 in. (36.2 x 8.9 cm) • Pressure ≤725 psi • CGA C-10 connection"
Recommended Gases	All gases offered in UNI sensors except for ozone, chlorine dioxide, hydrogen chloride, and hydrogen fluoride
Safety Certifications	For use in non-hazardous locations
Warranty	1 year



t +61 8 6108 0000

e info@gastech.com

w gastech.com

HEAD OFFICE
24 Baretta Road
Wangara WA 6065
Phone: +61 8 6108 0000

SYDNEY OFFICE
21/25 Narabang Way
Belrose NSW 2085
Phone: +61 2 9451 0054

BRISBANE OFFICE
PO Box 349
Cannon Hill Qld 4170
Phone: +61 7 3160 0901