

ION TIGER XT

Rapid, accurate detection of Volatile Organic Compounds (VOCs), within the most challenging environments.

The Tiger XT's photoionisation detection (PID) technology has been independently verified as best performing on the market for speed, accuracy, resistance to humidity and contamination, thanks to its patented Fence Electrode Technology. Its patented Fence Electrode Technology and anti-contamination design ensures optimal performance within humid and heavily contaminated atmospheres, extending run time in the field.

The Tiger XT is the most advanced handheld VOC detector on the market with the widest measurement range, accurately detecting gases down to 1 part per billion (ppb) up to 20,000 part per million (ppm). Tiger has the fastest response time on the market of just two seconds, and is as quick to clear down. The Tiger XT handheld VOC gas detector can detect over 750 VOCs and toxic compounds.

UPGRADEABLE FEATURES

The Tiger XT is fully upgradeable, this allows users to add further functionality if required. Upgradeable features include Health and Safety mode, PPB Sensitivity, Data Logging, Single Log Only (Push to Log) and Multi Log Only. Tiger XT is fully upgradeable without having to return the instrument to the factory.

TYPICAL APPLICATIONS

Typical applications for the Tiger XT include: Environmental Monitoring, Soil Contamination

Detection, VOCs in Landfill, Confined Space Entry, Emergency Response, Wing Tank Entry, Medical Gases within Hospitals and Fugitive Emissions.

5 YEAR EXTENDED WARRANTY

The Tiger XT can be registered online which extends warranty to up to 5 years. Register your instrument online within one month of purchase to extend the warranty.



KEY FEATURES

- **Improved Robust Design** – The instrument's rugged body can withstand harsh environments
- **Large Internal Gas Table** – Internal gas table has over 750 VOCs & toxic compounds
- **IP65 Ingress Protection** – Protection against a range of conditions and weather temperatures
- **Fast Response Time & Clear Down** – <2 second response time, one of the fastest and most accurate on the market
- **Instantaneous Alarms** – Bright visible alarms: RED & AMBER with loud sounder (95 dBA at 300 mm (12"))
- **Humidity Resistant and Anti-Contamination Design** – Patented Fence Electrode Technology ensures optimal performance and extends run time

ION TIGER XT

PERFORMANCE*

	10.6eV	11.7eV
Minimum Sensitivity***	1 ppb or 0.001 mg/m ³	0.6 ppm (600 ppb)
Maximum Reading (Range)**	20,000 ppm or 20,000 mg/m ³ ***	9,000 ppm ***#
Accuracy ***	± 5% or ± one digit	± 12% displayreading
Response Time T90 (s)	< 2 seconds	< 6 seconds
Lamp Lifetime	10,000 hours	≥500 hours****
Temperature Range	-20°C to +60°C	0°C to +60°C

*Model and gas dependent.

**Maximum reading is achieved with certain analytes such as ethanol.

***Specifications are based on isobutylene calibrations at 20 °C and 1000mBar.

All specifications quoted are at calibration point and under the same ambient conditions.

**** Based on continuous running.

#For indicative measurement only. Quoted accuracy achievable up to 2,000 ppm. For more accurate detection, calibration around concentration of interest is recommended.

Tiger XT V1.0. This publication is not intended to form the basis of a contract and specifications can change without notice.

SPECIFICATIONS Specifications subject to change without notice

Intrinsically safe approvals	<ul style="list-style-type: none"> Ex II 1G Ex ia IIC T4 Ga Tamb = -25 °C ≤ Ta ≤ +45 °C (with lithium ion battery pack) Tamb = -25 °C ≤ Ta ≤ +40 °C (with alkaline battery pack) ITS-I22ATEX3511X IECEX ITS 22.0025X ITS22UKEX0635X 3193491 conforms to UL Std. 913, 61010-1 Certified to CAN/CSA Std. C22.2 No. 61010-1 Class 1 Division 1. Approval for Groups A, B, C & D, T4 	Communication	Direct USB 1.1 connection
Humidity	0-99% RH (non condensing)	Calibration	2 and 3 point calibration (via calibration kit accessory)
Lamps	10.6 eV Krypton PID lamp (standard.) 10.0 eV and 11.7 eV lamps available	Battery life	Li-ion: Typical operating time of up to 24 hours Charge time: Typically 8 hours Alkaline: 3 x AA, typically 8.5 hours life
Data logging	120,000 points including date and time stamp	Flow Rate	≥ 220 ml/min (with blocked flow alarm)
		Ingress Protection	Designed to IP65 EMC tested to EN61326-1:2013 & EN50270:2015 & CFR 47:2008 Class A
		Alarm	<ul style="list-style-type: none"> Flashing LEDs Amber (low alarm) Red (high alarm) Sounder 95 dBA at 300 mm (12") Vibration on alarm Pre-programmed TWA and STEL*
		Dimensions & Weight	Width: 91 x Height: 370 x Depth: 60 mm Weight 870g



t +61 8 6108 0000

e info@gastech.com

w gastech.com

HEAD OFFICE
24 Baretta Road
Wangara WA 6065
Phone: +61 8 6108 0000

SYDNEY OFFICE
21/25 Narabang Way
Belrose NSW 2085
Phone: +61 2 9451 0054

BRISBANE OFFICE
PO Box 59
Kippa-Ring Qld 4021
Phone: +61 7 3160 0901