

Honeywell

SEARCHLINE EXCEL™ PLUS

Flammable Hydrocarbon gas detector



The Searchline Excel™ Plus Flammable Hydrocarbon gas detector delivers unsurpassed uptime with robust detection in some of the harshest conditions.

MAXIMIZE SAFETY COVERAGE EVEN IN MINIMAL VISIBILITY

Ensure optimal fire and gas safety by deploying cutting-edge optical gas detection that can see through even thick fog better than any other open path gas detectors whether NDIR or laser-based.

The Searchline Excel™ Plus is a medium-range gas detector designed for global oil and gas applications, upstream and downstream, onshore and offshore that protects your people, your facilities and your systems from combustible gas leaks.

KEY FEATURES

- **RELIABLE DETECTION**
Fast response to flammable Hydrocarbon gas even in low visibility conditions. Advanced diagnostics including window clarity and alignment accuracy to enable maximum uptime and continuous site protection.
- **HEAVY DUTY OPERATION**
Operates in harsh environments to maintain coverage. Advanced transmitter and receiver optics means that monitoring continues in thick fog long after other detectors cease to provide coverage.
- **AT-A-GLANCE INSTRUMENT STATUS**
High Visibility LED HALO ring provides clear indication of device status. Automatic reporting with full logging of alarms, events and maintenance actions.
- **EASY TO USE**
Low maintenance and calibration free. New Honeywell Fixed Platform Universal Mount and advanced alignment scope makes for easy mechanical installation.
- **MULTIPLE OUTPUTS**
Multiple outputs including 4-20mA, Relays, HART®, Modbus and Bluetooth® communication.
Easily integrate the Searchline Excel™ Plus into your existing network.
- **CONNECTIVITY**
Incorporates Bluetooth® connectivity for simplified, non-intrusive set-up and maintenance. Just pair the Searchline Excel™ Plus with our intrinsically safe, ruggedized mobile phone; then use the Honeywell Fixed Platform App to interact with the detector.

SEARCHLINE EXCEL™ PLUS

SPECIFICATIONS Specifications subject to change without notice

Primary Gases (Performance approved 1, 2)	Excel™ Plus will respond to a wide range of Hydrocarbon Gases as most of these gases absorb IR in the required wavelengths: Methane ^{1,2} , Ethane ¹ , Propane ^{1,2} , Butane ¹ , Pentane ¹ , Hexane, Ethylene ¹ , Propylene ¹ ; 1FM Performance Approved; 2DNV approved	Relay Outputs	Max. 32 Vdc/ac, max. 2 A resistive load
Range	0–5 LEL.m; for ppm.m equivalents see manual	Humidity	0–99% Relative Humidity Non-condensing, DNVGL-CG-0339 Location Class B
Recommended Alarm Setting	Low 1 LEL.m; High 3 LEL.m; for ppm.m equivalents see manual	Pressure	91.5-105.5 kPa (915–1055 mBar, non-compensated)
Recommended Minimum Alarm Setting	LEL.m; for ppm.m equivalents see manual	Repeatability	±0.4 LEL.m; for ppm.m equivalents see manual
Path Length	2 m to 120 m (6 ft to 393 ft)	Temperature Drift -40°C to +65°C (-40°F to 149 °F)	±0.2 LEL.m @ zero ±0.5 LEL.m @ 3 LEL.m
Speed of Response	T90 less than 3 seconds	Warm-up Time	Less than 5 minutes (operational), less than 1 hour (fully stabilized)
Analog Output Signal	4–20 mA Normal operation, 1 mA Fault*, 2 mA Inhibit, 3 mA Warning, 21 mA Over-range. Linearized 0–5 LEL.m	Internal Battery Cell	TLH-2450, 10-year lifetime (replaced only by authorized service)
Environmental Operating Temperature	-55°C to +75°C (-67°F to 167°F). DN-VGL-CG-0339 Location Class B	Weight	Searchline Excel™ Plus: Rx 6.1 kg (13.4 lb), Tx 6.0 kg (13.2 lb) Universal Mounting Bracket: 3.1 kg (6.9 lb) Stainless Steel Mount Plate Adaptor: 3.71 kg (8.18 lb) Stainless Steel
Storage Temperature Range	-55°C to +75°C (-67°F to 167°F). DN-VGL-CG-0339 Location Class B	Dimensions	Searchline Excel™ Plus: 103 mm dia x 325 mm x 180 mm (4.06 in dia x 12.8 in x 7.09 in) Universal Mounting Bracket: 165 mm x 165 mm x 130 mm (6.5 in x 6.5 in x 5.12 in) Mount Plate Adaptor: 210 mm x 210 mm x 127 mm (8.23 in x 8.23 in x 5 in)
Power Supply	24 Vdc nominal (18 Vdc to 32 Vdc)	Ingress Protection	IP 66/67 (Type 4X, in accordance with NEMA 250); Resistance to salt mist and sulfuric atmosphere (15-60 minutes exposure to salt air/mist; 15-60 minutes to sulfuric atmosphere)
Power Consumption (Average RMS)	Transmitter: Above +30°C (+86°F) = 3.8 W; +30°C to -30°C (+86°F to -22°F) = 5.6 W; Below -30°C (-22°F) = 11.8 W Receiver: Above +30°C (+86°F) = 3.0 W; +30°C to -30°C (+86°F to -22°F) = 4.8 W; Below -30°C (-22°F) = 7.4 W		
Output Signals	4–20 mA with HART®, Fault relay, Alarm 1 relay, Alarm 2 relay, Modbus, Bluetooth® (range up to 20 m (66 ft), depends on mobile device and environmental conditions)		

Safety Approvals**cULus:**

Class I, Division 1, Groups. B,C,D, T4, Ta -55°C to 75°C (-67°F to 167°F) Class II, Division 1, Groups. E,F,G, T4, Ta -55°C to 55°C (-67°F to 131°F) Class III Div. 1; Class I Zone 1 AEx db ia IIC T4 Gb, Ta -55°C to 75°C (-67°F to 167°F) Class I Zone 1 AEx db eb ia IIC T4 Gb, Ta -55°C to 75°C (-67°F to 167°F) Zone 21 AEx tb IIIC T100°C Db, Ta -55°C to 55°C (-67°F to 131°F); Um = 250 Vrms

IECEX:

IECEX ULD 18.0016X; Ex db ia IIC T4 Gb (for flameproof Ex d installations)
Ex db eb ia IIC T4 Gb (for increased safety Ex e installations) Ex tb IIIC 100°C Db
Tamb -55°C to 75°C (-67°F to 167°F); Um = 250 Vrms

Performance Approvals:

ANSI/FM/IEC/EN 60079-29-4

Functional Safety (SIL):

SIL 2 certified by TÜV (SÜD) to EN61508

Core Approvals


EN 50270: (EMC) IEC/EN 61000-6-4; Radio Equipment Directive 2014/53/EU
IEC/EN/UL/CSA 61010 (Electrical Safety); FCC / IC; RoHS, China RoHS

SEARCHLINE EXCEL™ PLUS

PART NUMBERS

Part Number	Version	Material	Entries	Approvals	Reserved
SLXL	P - Medium Range Continuous Safety Open Path Flammable Gas Detector	S = Stainless Steel	M = M25 N = 3/4" NPT	G = Global (ATEX, IECEx, UL, Marine, INMETRO, CCCF, etc.)	X = KIT D = Demo R = RX T = TX
SLXL-ESMGXX	Searchline Excel™ Edge, Long Range: SS M25 including Small SS Mount & Bracket & Plastic Sunshade				
SLXL-ESNGXX	Searchline Excel™ Edge, Long Range: SS 3/4" NPT including Small SS Mount & Bracket & Plastic Sunshade				


ACCESSORIES


Part Number	Description
2331B1020	Large Adjustable Mounting Bracket
2017B0113	Stainless Steel Sunshade
2017B0299	Alignment Scope
2017B0218	Functional Test Filters
2017D0226	Functional Test Filters Extender
2017B0185	Gassing Test Cell
188-200-010	Intrinsically Safe Android Device Ex02-Z1-C1D1/ATEX/IECEx/NEC - with camera
188-200-020	Intrinsically Safe Android Device Ex02-Z1-C1D1/ATEX/IECEx/NEC - without camera
188-200-120	Charger (EU/UK/US/AU) for 188-200-010 and 188-200-020
188-200-130	Vehicle Charger for 188-200-010 and 188-200-020
Free Download	Honeywell Fixed Platform App 

SPARES

Part Number	Description
2331B1100	Spare Universal Mounting Bracket Plate
2017B0112	Spare Standard Sunshade (Plastic)
2331B1150	Spare Terminal Block Set (5 Pack)
2331B1160	Spare Antenna Cover (5 Pack)



 +61 8 6108 0000

 info@gastech.com

 gastech.com

HEAD OFFICE
24 Baretta Road
Wangara WA 6065
Phone: +61 8 6108 0000

SYDNEY OFFICE
Suite G01, 10 Tilley Lane,-
Frenchs Forest, NSW, 2086
Phone: +61 2 9451 0054

BRISBANE OFFICE
PO Box 59
Kippa-Ring Qld 4021
Phone: +61 7 3160 0901