

BW™ ICON+

Multi-gas Detector

Serviceable four-gas detector with a choice of six sensors — BW™ Icon+ delivers an icon-based experience in a serviceable package. It enables you to maximize the lifespan of your four-gas detectors, optimize long-term cost of ownership and select from multiple gas sensors for flexible applications.

ICON DISPLAY FOR FAST DECISIONS

Like the fixed-life BW™ Icon, BW™ Icon+ is named for its first-in-the-industry display of simple icons for gas levels and device status. That means no live gas readings for workers to interpret and no time-consuming training. Instead, when there's a gas alarm, the bell icon on the display will illuminate, along with an indicator next to the sensor in alarm, so workers can quickly clear the area.

INTELLIGENT SENSORS FOR PREDICTIVE MAINTENANCE

How much life is remaining in the H₂S sensor, based on its age and gas exposure? When does the O₂ sensor need to be calibrated? Honeywell BW™ Icon+ has i-Series intelligent sensors that answer these kinds of questions, so you can take action and prevent unexpected downtime.

REPORTING AND ANALYSIS FROM YOUR SMARTPHONE

Want to see the full concentration of a gas or other information not on the icon-based display? Need to report a gas alarm? Simply download the Honeywell Safety Suite Device Configurator app, use Bluetooth® to pair your smartphone with the detector, and open the app to see the data — all organized in a report that's ready to send.



KEY FEATURES

- **RELIABLE** – Two months of battery runtime on a 4.5-hour charge — and up to four months if you turn off the detector at the end of each shift. No daily charging, no unexpected downtime.
- **EASY TO MANAGE** — The IntelliFlash™ green light indicates when the detector is in compliance and the amber light indicates the need for maintenance.
- **COMPATIBLE** – The BW™ Icon+ is compatible with the IntelliDoX instrument management system and Honeywell Safety Suite and also with TouchConnect™ using Bluetooth® for wireless configuration.
- **RESPONSIVE** – 1series sensors respond to dangerous gas levels in seconds, even in harsh temperatures.
- **ACCURATE** – Low-power infrared LEL sensor is immune to silicone poisoning, which means accurate monitoring of combustibles.
- **EASY TO USE** – Small, lightweight and wearable. One-button operation.

BW™ ICON+

SENSOR SPECIFICATIONS

Gas Name	Measuring Range	Resolution	Working Temperature
CO	0 to 2000 ppm	1 ppm	-40°C to 60°C (-40°F to 140°F)
H ₂ S	0 to 200 ppm	1 ppm (can set to 0.1ppm)	-40°C to 60°C (-40°F to 140°F)
SO ₂	0 to 150 ppm	0.1 ppm	-20°C to 50°C (-4°F to 122°F) intermittent -40°C to 55°C (-40°F to 131°F)
O ₂	0 to 30% VOL	0.1% VOL	-40°C to 60°C (-40°F to 140°F)
NDIR-CH ₄	0 to 100% LEL	1% LEL	-40°C to 60°C (-40°F to 140°F)

SPECIFICATIONS Specifications subject to change without notice

Size	108.2 mm x 61.5 mm x 43.2 mm (4.29 in x 2.44 in x 1.7 in) with Alligator Clip 108.2 mm x 61.5 mm x 37.8 mm (4.29 in x 2.44 in x 1.49 in) with Klick Fast Stud
Weight	185 g (6.5 oz) with Alligator Clip, 169 g (6 oz) with Klick Fast Stud
Working Temperature	-40°C to 60°C (-40°F to 140°F)
Working Humidity	5% to 95%
Ingress Protection	IP66, IP68
Alarms and Type	Visual, vibrating, audible (95 dB); Low, High, TWA, STEL, Negative Drift, Over Limit, Multi-alarm
Self-Test	Perform diagnostic of sensor, circuitry on activation; Activated detector automatically performs analog sensor diagnostic every 10 minutes, digital sensor diagnostic every second
Typical Battery Life	Two months (with NDIR CH ₄ sensor)
Connected Worker	Bluetooth® Low Energy (BLE) – Ability to connect to Honeywell's Safety Communicator App, Device Configurator App and Safety Suite Device Configurator Software
User options	<ul style="list-style-type: none"> • Change High, Low, TWA and STEL alarm set points • Latching alarms • Set Calibration and/or bump test reminders • Assign worker and location assignments • Always on User options only available via Device Configurator and Safety Suite Device Configurator
Certifications and Approvals	ATEX, IEC Ex, contains FCCID, contains IC
Device Warranty	Three-year warranty for sensors and detector



t +61 8 6108 0000

e info@gastech.com

w gastech.com

HEAD OFFICE
24 Baretta Road
Wangara WA 6065
Phone: +61 8 6108 0000

SYDNEY OFFICE
21/25 Narabang Way
Belrose NSW 2085
Phone: +61 2 9451 0054

BRISBANE OFFICE
PO Box 349
Cannon Hill Qld 4170
Phone: +61 7 3160 0901