EchoView Host

Mini-Controller for Wireless Monitors



Mini-Controller for Closed-Loop Wireless Solutions for Portable Gas Monitors

The EchoView Host mini-controller is the cornerstone of RAE Systems' Closed-Loop Wireless Solutions for portable gas monitors. This rugged handheld device can establish a self-contained wireless network with up to eight supported RAE Systems portable monitors and display their readings and alarm status in real time on an easy-to-read screen.

RAE Systems' Closed-Loop Wireless Solutions provide safety professionals real-time access to the readings and alarm status of workers' gas monitors to enable faster incident response. Safety officers who may not be directly at the scene can now have the same real-time visibility as those in the "hot zone."


Key Features

- Establishes a closed-loop wireless network with and displays real-time readings and alarm status of up to eight portable gas monitors at the same time
- Communication range extendable to 0.6 mi
 (1 km) with Mesh Routers
- Field-replaceable battery with a 10-day runtime
- Bright-red high-visibility alarm lights
- Loud audible alarm, 90dB @ 30cm
- Highly-resistant to electromagnetic and radio interference
- IP-65 water and dust ingress protection rating


Applications

- Aircraft maintenance (wing tank entry)
- Confined space entry
- Environmental
- Fire service
- HazMat response
- Refinery turnarounds

RAE Systems' Closed-Loop Wireless Solutions for Portable Gas Monitors with EchoView Host Mini-controller









EchoView Host

Mini-Controller for Wireless Monitors

- Remote wireless access to real-time readings and alarm status of portable gas monitors for faster incident response
- Supported wireless gas monitors:
 - ToxiRAE Pro PID
 - ToxiRAE Pro LEL
 - ToxiRAE Pro (for toxic gases and oxygen)
 - MultiRAE Lite (pumped and diffusion)
 - MultiRAE
 - MultiRAE Pro
- Intrinsically safe for Class I, Division 1 hazardous environments

Specifications*

Weight

Keypad Display 1.3 lbs (0.6 kg)

Visual Alarm

2 super-bright red LED lights

Audible Alarm

90dB @ 30cm

Wireless Network Wireless Frequency **RAE Systems Dedicated Wireless Network**

ISM license-free bands

Wireless Range (Typical)

- 990 feet (300 meters) - EchoView to Mesh Router

10.5" L x 3.7" W x 2.1" H (26.5 cm x 9.5 cm x 5.5 cm)

- 330 feet (100 meters) - EchoView to ToxiRAE Pro or MultiRAE Three operation and programming keys

Backlit LCD (1" x 1.5" / 72mm x 108mm)

Power Supply Disposable Lithium battery

Operating Time 10 days, 24/7 Operating Temperature

-4° to 122° F (-20° to +50° C)

Humidity 10% to 90% relative humidity, non-condensing IP Rating

Certifications

US and Canada: Class I, Division 1, Groups A, B, C and D, T4

Europe: ATEX IM1/II 1G Ex ia I/IIC T4

IECEx Ex ia I/IIC T4

RF Certifications

FCC Part 15, CE. Contact manufacturer for country-specific wireless

certification

Warranty 1 year

*Specifications are subject to change.

HEAD OFFICE Telephone +61 8 6108 0000 Facsimile +61 8 9408 1868 Email info@gastech.com.au 24 Baretta Road

Wangara, Western Australia 6065 Specifications subject to change without notice (Nov14)

NSW OFFICE Telephone +61 2 9451 0054 Facsimile +61 2 9450 0833 Email info@gastech.com.au 21/25, Narabang Way Belrose NSW 2085

