

PRODUCT BULLETIN

27 April 2021

Issue 21-4.1

Introducing the Tango® TX2 Two-Gas Monitor

Industrial Scientific is pleased to announce the global launch of the Tango® TX2, a light weight, reliable, two-gas monitor. The Tango TX2 increases site safety by allowing chemical manufacturing, oil and gas, and mining organizations to detect two gases with a single monitor instead of leaving one gas hazard unmonitored or requiring their employees to wear and maintain two single gas monitors.

With the use of individual sensors instead of combination sensors, the Tango TX2 is the most reliable two-gas monitor on the market. Individual sensors increase alarm accuracy, improve exposure data quality, and reduce unnecessary shutdowns from false alarms. A single, replaceable battery with a two-year life span minimizes the time spent managing gas detector fleets. With minimal maintenance, companies can easily assign each user a Tango TX2, giving workers an added sense of ownership and trust with their monitor.



The Tango TX2 is available globally in the following sensor configurations:

Part Number	Description
TX2-12011	Tango TX2, CO, H2S, English
TX2-14011	Tango TX2, CO, NO2, English
TX2-15011	Tango TX2, CO, SO2, English
TX2-1G011	Tango TX2, CO, CO Low, English
TX2-24011	Tango TX2, H2S, NO2, English
TX2-25011	Tango TX2, H2S, SO2, English
TX2-2G011	Tango TX2, H2S, CO Low, English
TX2-45011	Tango TX2, NO2, SO2, English
TX2-4G011	Tango TX2, NO2, CO Low, English
TX2-5G011	Tango TX2, SO2, CO Low, English

For additional information on the Tango TX2, visit our website at <https://www.indsci.com/tango-TX2>, or contact your local Industrial Scientific representative. Contact information can be found at www.indsci.com/offices.

Sincerely,

Handwritten signature of Jason Kettler in black ink.

Jason Kettler
Product Manager, Instrumentation