

CLIP

Maintenance – free single gas detector



The BW Clip single-gas detector is the most user friendly, reliable and cost effective way to ensure safety, compliance and productivity.

It operates up to three years maintenance-free: Just turn the device on and let it run continuously – no need for calibration, sensor replacement, battery replacement or battery charging. This means great reliability and no downtime.

Don't use your unit that often? With the two-year BW Clip for H₂S or CO, you can put the device in a hibernation case when you're not using it for a week or more – effectively extending its life by that period of time. Great for turnarounds, short-term projects or employee leave.

The BW Clip uses advanced technology for safety, compliance and productivity.

It uses Surecell™, a unique dual reservoir sensor which dramatically improves performance, response time, and longevity compared to traditional electrochemical sensors and consistently delivers reliable instrument performance under the harshest of conditions.

Compatible with both the MicroDock II and the IntelliDox instrument manage-

ment system, the BW Clip ensures easy and accurate record keeping to keep you compliant.

Not only is the IntelliDox the fastest bump test in the industry but it allows configuration of alarm set points and maximum productivity by performing different tests for up to five BW clip units at once!

CONFIGURABLE OPTIONS

- Configuration of high and low alarm set points before the device is activated.
- Adjustment of alarm set points and other parameters as needed.
- Option to display gas reading during alarm.
- User settable bump test reminder.
- Option to display the Real Time Clock.

KEY FEATURES

- **Maintenance-free: no sensor or battery changes required**
- **Compact, lightweight design with one-button operation**
- **Designed for a range of harsh environments and extreme temperatures**
- **Hibernation mode with case accessory or IntelliDox**
- **Automated self-test of battery, sensor and electronics**
- **Wide angle flash**
- **Automatic logging of the 35 most recent gas events and bump test results**
- **Compatible with IntelliDox and Fleet Manager II software**
- **Affordable, low cost of ownership**

BW CLIP

OPTIONS & ACCESSORIES



IntelliDoX



Hard hat clip



Hibernation case

For a complete list of kits and accessories, please contact our friendly staff at GasTech

GASES DETECTED

Carbon Monoxide CO
 Hydrogen Sulphide H₂S
 Oxygen O₂
 Sulfur Dioxide SO₂

SPECIFICATIONS

Specifications subject to change without notice

Size	4.1 x 5 x 8.7 cm	Event logging	IP66/67
Weight	92 g	Warranty	2 or 3 years from activation under normal operation, plus 1 year shelf life (6 months for O ₂). Up to 3 years total for 2-year H ₂ S and CO detectors when used with the hibernation feature, limited to 24 months of detector operation
Operating temperature (H₂S)	-40°C to +50°C	Certifications	cULus: Class I, Div. 1, Gr. A, B, C, D; Class I, Zone 0, Gr. IIC. ATEX: II 1G Ex ia IIC T4 Ga. IECEx: Ex ia IIC T4 Ga. CE; American Bureau of Shipping; CU TR Ex.
Operating temperature (CO)	-30°C to +50°C		
Operating temperature (O₂)	-20°C to +50°C		
Operating temperature (SO₂)	-30°C to +50°C		
Humidity	5 to 95% RH, non-condensing		
Alarms	Visual, vibrating, audible (95 dB), Low and High alarms. Automated internal diagnostic test every 24 hours once activated		
Typical battery life	2 years (H ₂ S, CO, O ₂ or SO ₂), 3 years (H ₂ S or CO)		



+61 8 6108 0000

info@gastech.com

gastech.com

HEAD OFFICE
 24 Baretta Road
 Wangara WA 6065
 Phone: +61 8 6108 0000

NSW OFFICE
 Suite G01,10 Tilley Lane,
 Frenchs Forest, NSW, 2086
 Phone: +61 2 9451 0054

QLD OFFICE
 Highfields, 4352
 Phone: +61 7 3160 0901